



Key features

- Data/Video combo logger
- Compact size
- Reusable (Rechargeable battery)
- Programmable start time
- Available option video illuminated by red/white LED light



DVL400M028-VD3GT



DVL400M130-VD3GT

Examples of Application

- Since the logger provides behavioral data and surrounding images of a tagged animal simultaneously, it is most suitable to investigate hunting behavior, feeding behavior and feeding ecology.

Technical Specifications			
Sensor	Movie, Acceleration in 3D, temperature, pressure	Depth range	0 - 400m
Size (length × wide × height)	57mm × 21mm × 13mm (DVL400M028)	Depth resolution	0.1 m
	61mm × 21mm × 15mm (DVL400M065)	Range Acceleration of	± 3g
	71mm × 21mm × 23mm (DVL400M130)	Resolution of Acceleration	0.01g
Housing material	Epoxy resin	Water pressure resistance	400 m
Weight in air	20 g (DVL400M028)	Clock	User manual setting Accuracy: ± Several seconds / day
	33 g (DVL400M065)		
	52 g (DVL400M130)		
Video recording time (Continuous recording mode)	2 hours (DVL400M028 without light)	Frame Rate (Fixed)	30 fps (frames per second)
	5 hours (DVL400M065 without light)	Delay Timer	0 – 96 hours
	8-10 hours (DVL400M130 without light)	Delay Timer of video recording	0 – 10 hours
Recording duration of behavioral data	12 hours	Depth trigger	0 - 300m
Resolution	1280×960	Recording Mode	Continuous recording
Angle of View (in air/ in water)	Horizontal 43°, Vertical 33° /Horizontal 31°, Vertical 24°	Communication	Logger cables
Temperature range	-20~50° C	Battery	Rechargeable lithium polymer battery
Temperature resolution	0.1°C		

Related products

Logger cable (Model IF-DVL-MA) to set up

Logger cable (Model IF-DVL-MB) to download data

Software

Related Product



Logger cable (IF-DVL-MA)



Logger cable (IF-DVL-MB)

Specifications are subject to change with or without notice.

Little Leonardo Corporation

Asahishoten Bldg. 3F, 4-4, Honkomagome 1-chome, Bunkyo-Ku, Tokyo 113-0021 JAPAN
Tel +81 3 3946 2410; Fax +81 3 5395 1676; e-mail : dofleo@l-leo.com

DVL400M-VD3GT1604cat